


40M IR FIXED LENS BULLET CAMERA

I4-320IPE-36



1/2.8" CMOS Sensor
 2 Mega-Pixel
 True Day & Night (IR Cut Removable)
 H.265 (HEVC) Compression
 0 Lux (IR On) Min. Illumination

ONVIF
 True WDR
 3D Noise Reduction
 Motion Detection and Privacy Masking
 AI Analytics (DDA + Face Detection)

Audio Input
 3.6mm Fixed Lens
 40m IR Illumination
 PoE Support
 IP 67 Protection

Micro SD Card Support
 Technician Port

Specifications

Camera	Video	Model	I4-320IPE-36
		Image Sensor	1/2.8" CMOS (16:9)
		Effective Pixels	1920x1080
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	1-25/30FPS
		Day & Night	ICR
		Min. Illumination	Day: 0.1lux / Night: 0.005lux (@F1.6, AGC On) 0lux with IR on
	Audio	Audio compression	G.711A/G.711U
		Communication	One-way Audio
	Image Processing	Image Settings	AWB, AGC Adjustable, Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
		Image Enhancement	True WDR (120dB), BLC, HLC, ROI
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip
		Privacy Zone	Yes
		Motion Detection	Yes
Compression	Analytics	Object Detection (Sterile Area, Line Crossing, Object Counting), Face Detection (10 Faces per frame), Camera Tampering	
	Video Compression	H.265S/H.264S*, H.265+/H.264+/H.265/H.264/MJPEG**	
	Resolution	2MP / 1MP / D1 (704x576) / QVGA (480x240) / CIF (352x288)	
	Multi-Stream	Master Stream: 2MP (1920x1080) / 1MP (1280x720) (1~30fps) Sub-Stream: 1MP/QVGA/D1/CIF Third Stream: QVGA/D1/CIF (1~30fps)	
	Bit rate	64Kbps ~ 4Mbps@H.265 / 64Kbps ~ 6Mbps@H.264	
	Encode Mode	VBR/CBR	
	Image Quality	Five levels under VBR; Free adjustment under CBR	

Housing	IR Distance	40m (2 High Power IR LED)
	Lens (Field of View)	3.6mm Fixed Lens (89°)
	Iris	Fixed Iris
	Lens Mount	M12 Mount
	Protection Rate	Water Proof: IP67
	Bracket	3-Axis Bracket
Connectivity	Dimensions	220.8x79.4x81.2mm
	Weight(gross)	~650g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	No
	Audio Connectivity	Audio Input
	SD Card	Event/Schedule based Main/Sub-Stream recording (Up to 128Gb)
Network	Hard Reset Button	Yes
	Alarm	No
	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 10 users with multi-stream real time transmission
Others	Network Protocol	IPv4, IPv6, TCP, UDP, DHCP, NTP, DDNS, 802.1X, RTSP, Multicast, UPnP, Email, FTP, HTTPS, QoS, P2P
	ONVIF	Yes
	Ethernet	100Mbps
Others	PoE	Yes
	Power Supply	DC12V/~780mA / PoE/~7.4W
	Work Environment	-30°C~60°C, 10%~90% Humidity

*Main Stream Only, **Sub-Streams Only

