

PINHOLE LENS MINI CAMERA

MC-392IP543



1/3" CMOS Sensor
2 Mega-Pixel
True Day & Night (IR Cut Removable)
H.265 (HEVC) Compression
0.1 Lux Min. Illumination

ONVIF
True WDR / BLC / HLC
3D Noise Reduction
Motion Detection and Privacy Masking
4.3mm MP Pinhole Lens

DC12V Power Supply
Local Storage
1 Way Audio (Built-In Microphone)
CVBS

Specifications

Camera	Video	Model	MC-392IP543
		Image Sensor	1/3" CMOS
		Effective Pixels	1920×1080
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	1-25/30
		Day & Night	ICR
		Min. Illumination	0.1lux
	Audio	Audio compression	G711A/U
		Communication	One Way Audio
	Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto / Manual) Sharpness, Saturation, Brightness & Contrast Adjustable
Image Enhancement		True WDR / BLC / HLC / ROI	
Noise Reduction		3D-DNR	
Image Orientation		Mirror/Flip	
Privacy Zone		Yes	
Motion Detection		Yes	
Compression	Video Compression	H.265 / H.264	
	Resolution	1080P (1920x1080), 720P (1280x720), D1, CIF, 480x240	
	Multi-stream	1920x1080(1~30fps) / 1280x720(1~30fps) / D1(1~30fps) / CIF(1~30fps) / 480x240(1~30fps)	
	Bit rate	64Kbps ~ 10Mbps@H.265 / 128Kbps ~ 12Mbps@H.264	
	Encode Mode	VBR/CBR	
Image Quality	Five levels under VBR; Free adjustment under CBR		

Housing	IR Distance	N/A
	Lens	4.3mm Pinhole
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	None
	Bracket	1-Axis Bracket
	Dimensions	30mm×30mm×29.5mm
Connectivity	Weight(gross)	90g
	Network	RJ45
	Power	DC Socket
	Analog Video Output	CVBS (BNCx1)
	Mic Connectivity	Built-In Microphone
	SD Card	Support Event recording over TF (128GB Max)
	RS485	No
Network	Alarm	No
	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	ONVIF	Yes
Others	Ethernet	100Mbps
	PoE	Yes
Power Supply	Power Supply	DC12V/~150mA
	Work Environment	-10 C ~50 C , 10%~90% Humidity

